



Specialty



Available Colors: Burgundy, Gray, Blue, Brown, Black

Prelude™ is a scraper mat made up of a coarse loop-twisted non-absorbent fiber that can be placed outside the entrance to begin the removal of dirt and debris from foot traffic. These aggressive fibers resist crushing while entrapping debris and preventing it from entering the facility. This mat can be used as part of the coordinated “Stages” series. A heavyweight vinyl non-slip backing ensures minimum movement.


Test	Test Description	*Results
ASTM D6540	Accelerated Soiling Method	Based on Visual Inspection 4.5 - Vacuum Rating 5.0 - Rating After Extraction
ASTM D412	Breaking Load/Elongation	155.2 lbs/in ²
ASTM 5252-98a	Accelerated Wear - 4,000 cycles (Hexapod Tumble Drum Tester)	Appearance: 2.0 Color: 2.0
ASTM D3936-05	Delamination	Exceeds Backing Strength
ASTM D2240-02	Durometer (Hardness)	70
ASTM D1335-05	Tuft Bind of Pile Yarn	6.1 = Standard
CPSC FF 1-70	Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	Pass

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

07/2014

Appearance Rating Key	
5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change

- Aggressive scraping fibers - First section of “Stages” Entry Mat System
- Heavyweight vinyl non-slip backing
- Recommended and approved product as part of the GreenTRAX™ program for “Green Cleaning” environments (When used as part of the “Stages” system)
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6', 4' x 8'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes: In 3', 4', and 6' widths (up to 60')



Custom Sizes