

## PREMIUM GRADE CREPE PAPER MASKING TAPE

### TYPICAL APPLICATIONS

- Industrial and automotive paint applications that do not require the use of a bake oven
- General purpose masking where a premium performance tape is needed

### ADVANTAGES AND BENEFITS

- Conformability
- Easy unwind
- High tensile strength, yet flexible backing that makes it an excellent choice for industrial and automotive paint applications
- Good quick stick
- Resists water, solvents and oil

### CONSTRUCTION

Overall Grade/Function: Premium  
Backing: Natural-colored crepe paper  
Adhesive: Rubber-based

### COLOR(S)

 Natural (NAT)



### STANDARD WIDTH(S)

12 mm 18 mm 24 mm  
36 mm 48 mm 72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.7 N/10 mm
Adhesion to Stainless Steel	40 oz/in width	4.37 N/10 mm
Thickness	6.4 mils	0.16 mm
Elongation	9%	9%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape<sup>®</sup> is a registered trademark of Shurtape Technologies, LLC

Form# TDS-COL-00-10/18/2013