

DEF DRUM PUMP 6GKR5

TECHNICAL data sheet

DEF PUMP PACKAGE

DEF pump packages are engineered to transfer AdBlue (AUS32) Diesel Exhaust Fluid (DEF) directly from barrels, drums and Intermediate Bulk Containers (IBC). Packages include sealless pump, variable speed motor, dispensing nozzle (manual or auto-shut off), compatible hose and barrel adapter.

APPLICATIONS

- Diesel Exhaust Fluid

TECHNICAL SPECIFICATIONS	
Package	Motor, Pump, Hose, Barrel Adapter & Hand Nozzle
Motor Type	Air, 1/2 HP (370w)
Wetted Parts	SS316, PTFE, Polypropylene, Carbon, EPDM
Pump Length	39" (1000 mm) (Drums)
Discharge Hose	CarboBlue, 8ft (2,4 m), 3/4" (19 mm) I.D.
Hand Nozzle	Auto Shut-Off, 316SS
Maximum Flow Rate	8 GPM (30 LPM)
Maximum Viscosity	450 cps (mPas)
Maximum Temperature	130° F (55° C)
Shipping Weight	23 lbs. (10, 45 kg)
Package Number	6GKR5
Motor	6GKR5
Air Consumption	22 cfm @ 90 psi (10.4 L/sec @ 6, 2 bar)
Pump Tube	6GKR5

