

PIG® Latching Drum Lid with Fast-Latch Ring

#DRM1072 - For 55-gal. New & Reconditioned Open-head Steel • Hinged w/ One Hand Latch



The fastest, easiest installing latching drum lid you can buy, keeps your drums and hazwaste storage containers securely closed and in compliance with regs!

- Fast-latch ring makes installation easy on a new or reconditioned 55-gallon steel drums; no clumsy nut-and-bolt ring
- Adjustment rod lets ring expand to fit reconditioned drums with larger diameters
- Latching handle easily opens and closes with one hand
- Nitrile gasket and locking mechanism seal lid to help reduce vapor emissions and keep drum contents dry and secure
- Easy-access lid closes securely to help you meet haz-waste regs
- Hinge stops keep funnel lid upright when open
- Durable, chemical-resistant powder coat helps ensure long service life
- Lockable latch helps prevent unauthorized access
- Hinge pin is made for easy lid removal without loosening band around drum
- Multiple lid color options let you segregate drums for safe, compliant filling



New Pig

By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

One Pork Avenue • Tipton PA 16684-0304

© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: DRM1072 - Pg 1 of 3

DRM1072 Specifications

Style:	Hinged w/ One Hand Latch
Use With:	55-gal. New & Reconditioned Open-head Steel
Padlockable:	Yes with .25" shackle
Sold as:	1 per box
# per Pallet:	12
Composition:	Lid - Steel Gasket - Nitrile
UNSPSC:	24112112

Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

29 CFR 1910.134(a)(1) - Engineering controls should be used as a first step in controlling harmful dusts, fogs, fumes, mists, gases, smokes, sprays, or vapors in the workplace.

29 CFR 1910.106(e)(2)(i) - Flammable liquids need to be stored in closed containers that are sealed by a "lid or other device" that does not allow liquids or vapors to escape.

40 CFR 261.4 - Helps you comply with 40 CFR 261.4 requiring excluded solvent contaminated wipes to be accumulated and stored in closed containers while they are managed onsite.

29 CFR 1910.22(a) - All places of employment "shall be kept clean and dry and in a sanitary condition" and floors shall be kept clean and dry.

40 CFR 264.173 - Containers holding hazardous waste, "must always be closed during storage, except when it is necessary to add or remove waste."

40 CFR 264.1086(c)(1)(ii) - Level one containers must have closure devices that, "form a continuous barrier over the container openings." When these closure devices are in place, there can be, "no visible holes, gaps or other open spaces into the interior of the container."

40 CFR 262.34(c)(1) - Satellite Accumulation Areas allow generators of hazardous waste to accumulate as much as 55 gallons of hazardous waste or one quart of acutely hazardous waste in containers at or near the point of generation. The container must be kept closed when not in use, must be under the control of the operator generating the waste and must be properly labeled.

Technical Documents:

(Available at newpig.com)

Product Data Sheet (PDS)

Chemical Compatibility (CCG)



By Phone:
1-855-493-HOGS

Online:
newpig.com

Email:
hothogs@newpig.com

New Pig

One Pork Avenue • Tipton PA 16684-0304
© 2014 New Pig Corporation. All rights reserved.
PIG and the PIG logo are trademarks in the U.S. and other countries.

ITEM: DRM1072 - Pg 3 of 3